

Living

Features and Benefits



- ▣ Improved security and weather sealing.
- ▣ BBA Approved.
- ▣ Top hung available in 8", 10", 12", 16", 20" and 24" applications.
- ▣ Side hung available in 12" and 16" applications.
- ▣ Available in Austenitic & Ferretic stainless steel.
- ▣ Manufactured in the UK.
- ▣ Egress Option.
- ▣ BSEN ISO 9001/2015 Quality Management

System. Technical Information

Size Ins	Size MM	Application	Window Size Approx Width MM	Window Size Approx Height MM	Window Weight Approx	Stack Height MM	Opening Angle
8	210	Top Hung	1200	300	10	13/14 & 16/17	62
10	260	Top Hung	1200	450	16	13/14 & 16/17	56
12	311	Top Hung	1200	600	21	13/14 & 16/17	64
16	406	Top Hung	1200	750	22	13/14 & 16/17	51
16	406	Side Hung	700	1300	24	13/14 & 16/17	51
20	511	Top Hung	1200	900	24	13/14 & 16/17	42
24	615	Top Hung	1200	1500	50	13/14 & 16/17	38
12	311	Top/Side Hung	650	1250	20	13/14 & 16/17	60
16	406	Top/Side Hung	700	1300	28	13/14 & 16/17	52
10	260	Top Hung	1200	450	16	13/14 & 16/17	90
12	304	Side Hung	800	1000	26	13/14 & 16/17	86
16	406	Top Hung	1200	750	22	13/14 & 16/17	83
16	406	Side Hung	700	1300	24	13/14 & 16/17	83

Assessment Data

Performance: 30,000 cycle guarantee.
Corrosion resistance Austenitic: 240 Hours
Corrosion resistance Ferretic: 90 Hours

Additional Information

Box Qty: 25/50 pcs per box

It is the responsibility of the window manufacturer to ensure that the finished window meets any required safety and performance specifications.

WINLOCK

Halesfield 8, Telford, Shropshire, TF7 4ES.

Tel: 01952 680178 Fax: 01952 684355

Sales: 01952 686777

Email: sales@winlock.co.uk

Web: www.winlock.co.uk

Sinidex Friction Stay
Window & Door Hardware Solutions

